Serial No. 09/754,018

Amendments to the Claims

1.   (currently amended) A control program for controlling an operation of a microprocessor, the control program comprising a concealed program recoverable by a data scramble circuit and a non-concealed program, wherein the data scramble circuit is a hardware circuit and acts as a part of an error correction circuit.

2.   (original) A control program according to claim 1, wherein a recovered program recovered from the concealed program includes:
        at least one function; and
        a relative address list indicating a relative address of the at least one function in the recovered program, wherein the relative address list is provided at a prescribed location in the recovered program.

3.   (currently amended) A device, comprising:
        a microprocessor;
        a program memory for storing a control program for controlling an operation of the microprocessor, the control program including a concealed program and a non-concealed program;
        a rewritable memory for storing a copy of the concealed program copied from the concealed program stored in the program memory; and
        a data scramble circuit for recovering the concealed program stored in the rewritable memory as a recovered program, wherein the data scramble circuit is a hardware circuit and acts as a part of an error correction circuit.

4.   (canceled)

5.   (original) A device according to claim 3, wherein the recovered program includes:
        at least one function; and
        a relative address list indicating a relative address of the at least one function in the recovered program, wherein the relative address list is provided at a prescribed location in the recovered program.

6.   (currently amended) A method for creating a control program, comprising:
        a program descramble step of descrambling a portion of a control program by reverse scramble of a data scramble circuit in a device to be

Page 2 of 6

Serial No. 09/754,018

controlled, thereby creating a concealed program as a portion of the control program; and

a program storing step of storing the control program including the concealed program in a program memory so that the control program controls an operation of a microprocessor in the device to be controlled, wherein the data scramble circuit is a hardware circuit <u>and acts as a part of an error correction circuit</u>.

7.   (original) A method for creating a control program according to claim 6, wherein the program descramble step includes the steps of:

creating a non-concealed program; and

synthesizing the concealed program and the non-concealed program into the control program.

8.   (currently amended) A method for operating a control program, comprising:

a program copying step of copying a concealed program which is a portion of the control program from a program memory into a rewritable memory;

a program recovery step of recovering the concealed program copied by the program copying step as a recovered program by a data scramble circuit; and

a program execution step of executing a non-concealed program included in the control program and the recovered program, wherein the data scramble circuit is a hardware circuit <u>and acts as a part of an error correction circuit</u>.

9.   (original) A method for operating a control program according to claim 8, further comprising a program erasure step of erasing the recovered program from the rewritable memory.

Page 3 of 6